

KEY FEATURES


- > Low voltage piezo ceramic
- > Optimal preload for high dynamics
- > Mechanical Amplification
- > Compact Size
- > High Resolution

RELATED PRODUCTS

- > CTEC benchtop controllers
- > CTEC OEM controllers

AVAILABLE OPTIONS

- > Vacuum compatibility
- > Non magnetic shell



NON CONTRACTUAL PICTURE

PARAMETER	VALUE	UNIT
> Quasistatic performances		
Nominal Stroke	34	µm
Min stroke	31	µm
Resolution ⁽¹⁾	1.9	nm
Blocked force	3.7	N
Stiffness	0.11	N/µm
> Dynamic performances		
Resonance frequency (free-free) ⁽²⁾	25000	Hz
Resonance frequency (blocked-free) ⁽³⁾	4 800	Hz
Force limit ⁽⁴⁾	7.5	N
> Control & driving		
Voltage range	-20 ... 150	V
Capacitance ⁽⁵⁾	0.043	µF
> Dimensions & interfaces		
Height	4	mm
Length	9	mm
Width incl wires	5	mm
Mass	0.15	g
> Standard mechanical interfaces	See ICD	
> Electrical interface	See ICD	

ANNOTATIONS


(1) Quasistatic excitation. With standard LA75 range amplifier. SNR=85 dB computed as RMS output signal / RMS output Noise floor at [0;200 Hz]

(2) Free-free: The actuator mounts are free

(3) Blocked-free: The actuator is fixed to a mechanical support assumed infinitely stiff

(4) Maximum pulling or pushing external force, valid up to 90% of the blocked-free resonance frequency of the actuator

> §§ (5) Capacitance +/- 20%, at 1 V RMS, low frequency, without load



Norme / standard : CEDRAT TECHNOLOGIES 59 Chemin du Vieux Chêne 38246 MEYLAN Cedex FRANCE TEL : 33 (0)4 56 58 04 00		Norme (s) : Ce document est la propriété de Cedrat TECHNOLOGIES. Il est strictement confidentiel et ne peut être reproduit, copié ou diffusé sans l'autorisation écrite préalable de Cedrat TECHNOLOGIES. This document is the property of Cedrat TECHNOLOGIES. It is strictly confidential and cannot be reproduced, copied or disseminated without the prior written consent of Cedrat TECHNOLOGIES.	
Référence / Reference : ICD APA30uXS NM H		Révision / Revision : Etat du document / Life cycle : 151	
Tolérances géométriques selon : Norme / tolerance according to : Echantillonnage / Sampling : Rayon raccord / Radius curvature : Auteur / Drawn : Vérifié / Checked : Approuvé / Approved :		Révision / Revision : Etat du document / Life cycle : 151 Format / Page : A3 / 1/1	
OKR Public		002550-ICD-01 C Applicable	