

APPLICATIONS

- > High accuracy displacement monitoring
- > High accuracy closed loop control

KEY-FEATURES

- > Output: $\pm 10V$ voltage
- > Accuracy 0.01%FS
- > 15kHz bandwidth
- > Up to 3 channels on a single board
- > Fully compatible with CTEC Strain Gauges and CTEC Powered Racks

RELATED PRODUCTS

- > CTEC Strain Gauge Sensors
- > CTEC Powered Racks



SPECIFICATIONS

PARAMETER	TYPICAL VALUE	UNIT
Number of channels	1 ... 3	
Input		
Sensor type	Full bridge, strain gauge-based, 4 wires	
Bridge impedance	350	Ω
Bridge excitation (1)	5	V
Gain span (2)	116 ... 2700	
Input sensitivity span @ $V_b = 5V$, FSO = $\pm 10V$ (3)	1.5 ... 34.5	mV/V
Input sensitivity span @ $V_b = 5V$, FSO = $-1..+7.5V$	0.6 ... 14.7	mV/V
Output		
Typical output voltage (4)	± 10	V
Output current	± 20	mA
Output impedance	100	Ω
DC offset span	± 10	V
Minimum output load	600	Ω
Bandwidth - 3dB	15	kHz
Accuracy		
Resolution	0,01	% FS (3)
Linearity	0,01	% FS
Thermal offset drift	± 0.025	% FS/°C
Thermal gain drift (5)	$\pm (8.5E-5 * G + 2.1E-2)$	%/°C
Thermal gain drift @ $G = 500$	± 0.06	%/°C
Thermal gain drift @ $G = 1000$	± 0.11	%/°C
Common Mode Rejection	> 100	dB

MISCELLANEOUS

PARAMETER	TYPICAL VALUE	UNIT
Mass	0,18	kg
Front face dimension	6F wide, 3U high	
Rack compatibility	Fully compatible with CTEC powered rack	
Operating temperature range	0 ... 40	°C
Storage temperature range	-10 ... 50	°C

INTERFACES

Output connector	BNC type
Input sensor connector	LEMO EGG.00.304.CLL
DC Offset	10-turn screw potentiometer

INCLUDED ACCESSORIES

Strain Gauge cable	Shielded 1.5m
--------------------	---------------

OPTIONS

Strain Gauge cable	Specific length on request
--------------------	----------------------------

ANNOTATIONS

- (1) Alternative voltage 2.5, 7.5, 10V available on request
- (2) Other values on request
- (3) FSO : Full Scale Output, FS : Full Scale
- (4) Set to [-1V ; 7.5V] on CTEC systems to be consistent with driver input
- (5) G : gain

DRAWINGS

